

This diode can be only used in constant voltage and current. Operating voltage and current, refer to the table in paragraph II. Please do not aim the laser to people or animal. You can observe the laser spot ...

The 940nm series laser diodes are fabricated in a hermetically sealed 14-pin butterfly package. The laser diodes contain a monitor photodiode, thermoelectric cooler (TEC), and a thermistor to secure ...

These fiber-coupled 940nm laser diodes are offered as stock items or associated with a CW or Pulsed Laser Diode Driver. They are compatible with our high speed nanosecond pulsed drivers or high ...

These fiber-coupled 940nm laser diodes are offered as stock items or associated with a CW or Pulsed Laser Diode Driver. They are compatible with our high ...

Please do not touch VD surface by naked hands or squeeze the sealant on VD surface, or it may cause wrong optical angle and distorted laser spot, even damage the VD.

High brightness, quality, and reliability are the foundation of our single-mode laser diode product family. Our 940nm single-mode laser diodes are capable of delivering output power up to 300mW.

940nm 25W Pulsed VCSEL Laser Diode Multimode VCSEL Low wavelength drift Oxide isolation technology Low threshold current High reliability Integrated photodiode

Wavespectrum offer 940nm 1w 2w 3w 4w 5W High Power Laser Diodes with C mount and TO3 Package

940nm laser diode Model 1a: 100mW / singlemode fiber / 14 pin Butterfly package / SMF or PMF Reference: 940LD-1a-0-0 (-1: SMF ; -2: PMF)

Laser diodes are classified based on continuous operation - Contact us for any special requests regarding classification or power limitation.

These single mode fiber-coupled Fabry-Perot laser diodes are centered at 940nm and offer output power up to 100mW. They are offered in an industry standard butterfly package which has a single ...

Web: <https://busydoniemiecwaldii.pl>